

HOW TO CHECK THE AIR PRESSURE IN YOUR PRESSURE TANK

CHECK AIR PRESSURE EVERY 12 MONTHS

- STEP 1** SWITCH THE PUMP OFF AT THE POWER POINT
- STEP 2** OPEN A WATER TAP AND RELEASE WATER PRESSURE
- STEP 3** LEAVE THIS TAP TURNED ON UNTIL YOU GET TO STEP 8
- STEP 4** CHECK THE AIR PRESSURE WITH A TYRE PRESSURE GAUGE
- NOTE: THE AIR PRESSURE VALVE IS MOST OFTEN LOCATED
AT THE TOP OF THE TANK UNDER A PLASTIC CAP WHICH
WILL UNSCREW*
- STEP 5** THE CORRECT AIR PRESSURE FOR THE TANK IS
10% BELOW THE CUT-IN (START PRESSURE) FOR YOUR PUMP
- _____ PSI OR _____ Kpa
- STEP 6** PUMP AIR INTO THE AIR VALVE USING A TYRE PUMP
OR COMPRESSOR
- STEP 7** CHECK THAT THE AIR PRESSURE IS SET CORRECTLY
- STEP 8** TURN OFF THE WATER TAP AND SWITCH THE PUMP ON

THE JOB IS NOW COMPLETE !

IF YOU REQUIRE ANY FUTHER INFORMATION PLEASE CONTACT US ON

(07) 4688 9222